z*		CENTRAL INTELL	IGENCE AGENCY	
		INFORMATIO	ON REPORT	
	COUNTRY	USSR	DATE DISTR. 26 Feb 1	.953
	SUBJECT	Railroad Rolling	Stock and Operations NO. OF PAGES 3 50	X1
	PLACE ACQUIRED		NO. OF ENCLS.	0X1
	DATE ACQUIRED	<u> </u>	SUPPLEMENT TO	
	DATE OF INFORMATIO	N .		
*	THIS DOCUMENT CONTAINS INFORMAT OF THE UNITED STATES, BITHIN TH AND 784, OF THE U.S. CODE, AS LATION OF ITS CONTENTS TO OR AS PROMIBITED BY LAB. THE REPRODU	RE MEANING OF TITLE 18, SECTIONS 783 IMENOED. ITS TRANSMISSION OR REVE- CCEIPT BY AN UNAUTHORIZED PERSON IS	THIS IS UNEVALUATED INFORMATION	
				}
				•
	The layin length of	ng of 7,230 kilometers of track to 123,000 kilome	946 to 1950 envisaged ambitious accomplist track was planned which would raise the sters. The construction of 7,585 steam lose also scheduled. The transport plans for	somo- r 1950
	The laying length of tives and called for 795 milli	ng of 7,230 kilometers of track to 123,000 kilome 1 472,000 freight cars we or 771 million tons of fr con tons were transported	, tamper, and a tributum trulucur minitor retion one	some- r 1950 tal of ilo-
	The laying length of tives and called for 795 milling meters. 115,000 co.	ng of 7,230 kilometers of track to 123,000 kilome 1 472,000 freight cars we or 771 million tons of fa lon tons were transported The average daily loading pars and this was exceeded know of any trend toward	ters. The construction of 7,585 steam loss also scheduled. The transport plans for eight and actually was surpassed, as a tell. This made a total of 600 billion ton king of freight cars for 1950 was planned as with a daily average of 118,000 cars.  Be Diesel or steam locomotives for the rail of the transport locations. In the southern	come- r 1950 tal of ilo- roads,
	The laying length of tives and called for 795 milling meters. 115,000 co.  2. I don't have the but there where the lecomotive of the second se	ng of 7,230 kilometers of track to 123,000 kilometers of 1472,000 freight cars we or 771 million tons of friend tons were transported the average daily loading ars and this was exceeded know of any trend towards is a large number of being a shortage of waters. It is my opinion the	track was planned which would raise the stars. The construction of 7,585 steam loss also scheduled. The transport plans for eight and actually was surpassed, as a test. This made a total of 600 billion ton king of freight cars for 1950 was planned as of with a daily average of 118,000 cars. In the southern of the types of locamotives. In the southern and coal there is a larger number of plant there will be more electrification of coal there will be more electrification of coal there will be more electrification of	somo- r 1950 tal of ilo- roads, areas esel the
	The laying length of tives and called for 795 milling meters.  115,000 co.  2. I den't lout there where the lecometic railread and he for the lecometic railread and an interest railread and an i	ng of 7,230 kilometers of track to 123,000 kilome 4,72,000 freight cars we for 771 million tons of falon tons were transported. The average daily loadingers and this was exceeded mow of any trend towards is a large number of bore is a shortage of water was. It is my opinion to lines. The reasons the pressed margin of profi-	ters. The construction of 7,585 steam locaters. The construction of 7,585 steam locates also scheduled. The transport plans for eight and actually was surpassed, as a tell. This made a total of 600 billion ton king of freight cars for 1950 was planned as a with a daily average of 118,000 cars.  The property of locations of the rail of the southern and coal there is a larger number of Direct are mainly in the convenience of opert. The increased construction of electric	somo- r 1950 tal of ilo- roads, areas esel the
	The laying length of tives and called for 795 milling meters.  115,000 c  2. I don't length the locomotion railread and an instations  3. I'm not colleve the I know the angle out of the Baku run	ng of 7,230 kilometers of track to 123,000 kilometers are 1472,000 freight cars we is 472,000 freight cars we for 771 million tons of free free free average daily loadingers and this was exceeded and of any trend towards is a large number of being a shortage of waters. It is my opinion to lines. The reasons the nereased margin of profisubstantiate this believes at there are such lines at there are such lines had there is such a lines to railroad from Mines had of these these electrifs to Surakhany Sabunchiy	track was planned which would release the stars. The construction of 7,585 steam loss also scheduled. The transport plans for eight and actually was surpassed, as a to the star and call cars for 1950 was planned as definite and cally average of 118,000 cars.  In the southern and coal there is a larger number of Direct are mainly in the souvenience of operations. The increased construction of electric cars mainly in the souvenience of operations.	roads, areas esel the ration power 50X1 be- ningrad. ere is far
	The laying length of tives and called for 795 milling meters.  115,000 c  2. I den't length the locometic railread and an instations  3. I'm not colleve the I know the an electron out of the Baku run motives colleves.	track to 123,000 kilometers of track to 123,000 kilometers to 1472,000 freight cars we at 472,000 freight cars we for 771 million tons of fallon tons were transported the average daily loadingers and this was exceeded mow of any trend towards is a large number of being a shortage of waters. It is my opinion to lines. The reasons then hereased margin of profisubstantiate this believes at there are such lines at there are such lines that there is such a line rice railroad from Mineral he offices these electrif s to Surakhany Sabunahiy extending into Baku.	ters. The construction of 7,585 steam loss also scheduled. The transport plans for sight and actually was surpassed, as a test. This made a total of 600 billion ton king of freight cars for 1950 was planned as definition of freight cars for 1950 was planned as edwith a daily average of 118,000 cars.  In the period of locomotives for the rail of types of locomotives. In the southern and coal there is a larger number of Director are mainly in the convenience of open there will be more electrification of refor are mainly in the convenience of open to increased construction of electric fiction in Mineralnye Vody. Grosny, Mosocw and Le in Baku.  In Baku.  In Baku.  In There is also a separate line for steam are used in transporting both freight are transported by the present there are generally in the convenience of part that the present there are generally in the convenience of the steam transporting both freight are transported by the present there are generally in the convenience of the present there are generally in the convenience of the present there are generally in the convenience of the present there are generally in the convenience of the present there are generally in the convenience of the present there are generally in the convenience of the present there are generally in the convenience of the present the present there are generally in the convenience of the present	roads, areas esel the ration power 50X1 be- ningrad. ere is far rom
	The laying length of tives and called for 795 milling meters. 115,000 co. 115,	ng of 7,230 kilometers of track to 123,000 kilometers are transported to the average daily loading are and this was exceeded to one of any trend towards are is a shortege of waters. It is my opinion to lines. The reasons them there are such lines at there is such a line realroad from Mineral he offices these electrif at the statement of the such a line realroad from Mineral he offices these electrif at the statement of the such a line realroad from Mineral he offices these electrif at the statement of the such as the such a line realroad from Mineral he offices these electrif at the statement of the such as the such a line realroad from Mineral he offices these electrif at the such as the such a line realroad from Mineral he offices these electrif at the such as the such	track was planned which would release the stars. The construction of 7,585 steam loss also scheduled. The transport plans for eight and actually was surpassed, as a total of 600 billion ton king of freight cars for 1950 was planned as defined with a daily average of 118,000 cars.  Be Diesel or steam locomotives for the rail of the types of locomotives. In the southern and coal there is a larger number of Director are mainly in the convenience of open to the increased construction of electric for the increased construction of electric for the increased construction of electric fined railroads at this time, but I in Mineralnye Vody. Grosny, Moscow and Le in Baku.  Inspecting to Moscow, but I am uncertain how ied lines extend. The electric railroad for the case is also a separate line for steam are used in transporting both freight ager trains, however, there are generally in the trains, whereas in the freight trains the the train.	roads, areas esel the ration power 50X1 be- mingrad. ere is, far rom a lose-
	The laying length of tives and called for 795 milling meters. 115,000 co. 115,000 co. 12. I don't have the lecomotive railroad and an instations  3. I'm not colleve the laneway the stations out of the Baku run motives cout of the Baku run for the stations cout of the Baku run for the stations cout of the Baku run for the Baku r	reach to 123,000 kilometers of track to 123,000 kilometers to 123,000 kilometers we at 472,000 freight cars we for 771 million tons of falen tons were transported the average daily loading are and this was exceeded to a large number of being a shortage of water is a shortage of well lines. The reasons them hereased margin of profistly substantiate this believes there are such lines at there are such lines at there are such lines at there is such a line ric railroad from Mineral he cities these electrifies to Surakhany Sabunchiy extending into Baku.  The electric locomotive realing and one your locomotive pulling real condition of passeng	ters. The construction of 7,585 steam loss also scheduled. The transport plans for eight and actually was surpassed, as a tell. This made a total of 600 billion ton king of freight cars for 1950 was planned as de with a daily average of 118,000 cars.  Be Diesel or steam locomotives for the rail of the types of locomotives. In the southern and coal there is a larger number of Diesel there will be more electrification of refor are mainly in the convenience of open to the increased construction of electric cars.  Electrified railroads at this time, but I in Mineralnye Vody. Grosny, Moscow and Le in Baku.  In Baku.  In the electric railroad for the railroad for the season. The electric railroad for the season as separate line for steam are used in transporting both freight ager trains, however, there are generally to pushing, whereas in the freight trains the	roads, areas esel the ration power 50X1 be- mingrad. ere is far rom loco- and two ley a lot le cars

50X1

only a very few comfortable cars. Passenger trains are generally twelve to fourteen cars in length and one of these cars, generally number six, is a so-called comfortable car. An increased fare is levied on people riding in this car. Often car number seven is also a comfortable car, but this car is reserved for military officers and it is very difficult to buy a ticket for it. If you have the money for the extra fare on car number six you can generally get a seat in that car.

- 6. Most of the passenger cars are of a type known as the platskartnyy vagon or a reserved seat car literally. The seats on this type of car are not reserved, however. This type of car is fitted out with bench-like seats which are arranged in various ways. The cars are divided into two or more sections and there are a varying number of seats in the individual compartments. The four-axle comfortable cars are about thirteen meters long and have eight sections which seat eight to ten people per section. The benches may be ticketed as seats for two or three people or the places may be sold as sleeping benches. In a four-axle car with three compartments there are about forty sleeping accompositions. Two-axle cars generally do not have any sections or divisions.
- 7. The bearings frequently burn out on these platskartnyy-type cars and are the chief cause for them being put out of operation.
- 8. There is another type of car which is used for transporting prisoners and it is called an arrestanskiy vagon. There is usually at least one of these cars on every train. As far as I know it is not used for transporting any one type of prisoner.
- 9. Since the end of World War II a two-year prison sentence has been established for unauthorized riding of a freight train.
- The condition of the rolling stock for hauling cargo is better than the passenger equipment and considerable effort is being made to further improve the quality and quantity of the former. The majority of the freight cars used to be of the two-axle type, but due to the concentration of production on the four-axle type, the latter are probably more numerous than the former. The basic types of rolling stock for transporting cargo are as follows:
  - Freight car (vagon) This is a closed freight car; the two-axle type is usually capable of hauling 16 to 20 tons of cargo and the four-axle type can haul 50 tons. This type of car is sometimes used as a cattle car, and in such cases air holes are opened in the car for ventilation.
  - Flat car (platform) This is an open flat car; the two-axle types can carry 16 to 20 tons and the four-axle type carries 50 tons. This type is also used as a cattle car and in such cases slats and a roof are constructed for protecting the livestock.
  - Gondola (gondola) This is an open freight car which is used in the transporting of cargo such as coal. This type car has four axles and can carry 50 to 60 tons.
  - Tank cars (tsistern) This is used for transporting petroleum products and liquid fuels and has either two or four axles, capable of carrying twenty or forty tone respectively.
  - Refrigerator car (kholodiknik) I think that this car is both the two and four-axle type, capable of carrying 20, 40, and 50 tons.
- With regard to the organization of the trains, I am not familiar with any rules governing the physical arrangement of pars. I do know that generally the freight cars carrying the more valuable and fragile cars are placed in the middle of the trains where the swaying is less pronounced than on the ends of the train. This type of cargo would incolude instruments, machinery and engines. Passenger cars are generally hauled in separate trains and are not included in freight trains. There is another general practice of a similar nature established for tank cars. The tank cars are usually hauled in separate trains and are not mingled with other types of freight cars. There are usually about fifty cars per train.
- 12. The majority of all types of rolling stock have air brakes (kazantsev) and also a Westinghouse brake. I heard that the Westinghouse brake was unreliable as it didn't brake steadily and tended to damage the wheels. I haven't seen this type of brake since the end of World War II. I saw some mechanical brakes on small cars, but all of the larger freight cars are equipped with airbrakes.
- There are frequent breakdowns in the operation of the trains in the USSR. This is principally due to the extremely heavy loads that the trains are obliged to haul. The heavy tonnage causes a rapid deterioration of rolling stock and track with resultant disruptions of service. The most frequent disruptions in operations coour as a result of cars leaving the tracks due to the uneven condition of the roadbeds. In the regions north of Saratov another major cause of accidents is the heavy snowfalls received in those regions two major railroad accidents which occurred and were then suppressed from the news. In the Summer or Spring of 1950 an accident happened near Pushkino (fermerly SECRET/SECURITY INFORMATION

\_\_\_\_5

Urbakh) when a train of cars parted from the locomotive near the top of a hill. The freight cars ran away and leaped the track in a railroad station. All of the freight and the 10 or 15 cars involved were a total loss. In the winter of 1949-1950 there was an unusually heavy snowfall in the area around Astrakhan. A passenger train was stranded in the snow drifts and a loss of 100 lives occurred. No mention of this disaster was ever printed in the newspapers.

in the Soviet Zone of Germany I saw no Soviet rolling stock in that area, nor have I ever seen any German rolling stock in the USSR. I suspected that a German plant near Leipzig was producing rolling stock for the Soviets, but I am not certain. As far as I know all Soviet trains are unloaded at the Soviet border and the cargo reloaded on trains of European gauge.

15. The only plants-which I know to be engaged in the production of rolling stock for the railroads are the Leningrad Railroad Car Building Plant i/n Egorov and the Bryansk Car Building Plant. I know nothing about the volumes of production of these plants.

- end -

50X1